

# TYREinflate 200



### Rapid Inflation Time

Inflate the tire to the desired pressure in ca. 4.5 minutes\*\*



### Wind-up Cable

Winding/unwinding mechanism for a neatly rolled up cable



### Including three-piece adaptor kit

To inflate bicycles, balls and other inflatables



### Rapid tyre inflator with wind-up cable

The OSRAM Tyreinflate 200 analogue tyre inflator inflates a 13" tyre from flat in up to 4.5 minutes\*\*. It has a large on/off button for easy use. Its stable design keeps the inflator still while in use. Powered from an in-car 12V socket, the Tyreinflate 200's long 3m power cable makes reaching all the tyres around the vehicles easier. Shows pressure readings in kPA, bar and PSI. Includes storage compartment for tyre valve caps when being used. Comes with three-piece adaptor set for use with bicycle tyres, motorcycle tyres, balls and other inflatables.\*\*based on inflating a 13" tyre from flat to 2.41 BAR

## Product family datasheet

### Technical data

	General Product Information	Electrical Data	Physical Attributes & Dimensions	
Product description	Global order reference	Nominal voltage	Height	Width
TYRE inflate 200	OTI200	11.1 V	180.0 mm	79.0 mm








		Operating Conditions	Additional product data	Capabilities
Product description	Length	Noise Level (dB)	Display Type	Fuse
TYRE inflate 200	197.0 mm	90 dB	Analogue	10 A

	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)			
Product description	Date of declaration	Candidate list substance 1	CAS No. of substance 1	Safe use instruction
TYRE inflate 200	19-10-2024	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.

Product description	Declaration no. in SCIP database
TYRE inflate 200	2c7125da-b121-4f3d-8c54-1fc45a571265 91681add-0e23-41d1-a9d2-68596b3c0670

## Product family datasheet

### Download Data

File	
	User instruction TYREinflate 200
	Movie application TyreInflate How to Video (RU)
	Product movie TyreInflate 200 Product Video (EN)
	Product movie TyreInflate How to Video (EN)
	Product movie TyreInflate How to Video (IT)
	Video OSRAM TYREinflate 200: Rapid tyre inflator with wind-up cable
	Video OSRAM TYREinflate How To: Change your vehicle's tyre pressure easily

#### Safety advice

Product won't exceed noise levels of more than 90 dB

#### Legal advice

CE and EAC compliant

\* for precise conditions please refer to: [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee)

\*\* based on inflating a 13" tyre from flat to 2.41 BAR

Application advice:  
For more detailed application information and graphics please see product datasheet.

Disclaimer:

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

#### Application advice

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.