


# LEDDriving HL BRIGHT H1



**Up to +300% more brightness**

More light allows to see farther and therefore react sooner. Signs, obstacles and hazards can be recognized sooner. Compared to minimum ECE R112, for H7/H18 & H4/H19



**Very compact LED replacement for conventional H1 high and low beam lamps**

Reduced glaring thanks to an optimized light distribution



**Cool White color temperature of 6,000 K**

Better visibility thanks to daylight effect



**4 year OSRAM guarantee**

For precise conditions, please refer to [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee)



**High-performing LED retrofit lamp providing improved visibility and a stylish look**

With up to +300% more brightness (compared to ECE R112, for H7/H18 & H4/H19), the OSRAM LEDDriving HL BRIGHT retrofit lamp ensures optimum visibility and thus allowing drivers to recognize signs, obstacles and hazards sooner than conventional lamps. This LED retrofit lamp not only creates a stylish modern look with a cool white color temperature of 6,000K but also offers reduced glaring thanks to an optimized light distribution. Premium OSRAM quality and LED technology grant up to 5 times more lifetime (compared to ECE R112) and better visibility thanks to daylight effect. The pair of lamps comes with a 4-year OSRAM guarantee. For precise guarantee conditions please refer to [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee). The LEDDriving HL BRIGHT high and low beam lamps by OSRAM replace conventional halogen lamps and are 12V compatible. With the latest LED technology and very compact design, these lamps allow a high compatibility and an easy installation for cars with the respective halogen lamp types. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

## Product family datasheet

### Technical data



| Product description                 | Product information  |                                     | General Product Information | Electrical Data |                 |
|-------------------------------------|--|-------------------------------------|-----------------------------|-----------------|-----------------|
|                                     | Application (Category and Product specific)                    | Product type (off-road vs. on-road) | Global order reference      | Power input     | Nominal voltage |
| LEDriving HL BRIGHT $\triangleq$ H1 | Mainly used for Low Beam, High Beam and Fog light applications | Off-road $\triangleq$ H1            | 64150DWBRT                  | 13 W            | 12.0 V          |

| Product description                 | Nominal wattage | Photometric Data      |                         | Physical Attributes & Dimensions | Lifetime Data |
|-------------------------------------|-----------------|-----------------------|-------------------------|----------------------------------|---------------|
|                                     |                 | Nominal luminous flux | Luminous flux tolerance | Diameter                         | Lifespan Tc   |
| LEDriving HL BRIGHT $\triangleq$ H1 | 13 W            | 1500 lm               | $\pm 20$ %              | 14.0 mm                          | 5000 hr       |

| Product description                 | Capabilities | Environmental & Regulatory Information<br>Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) |                            |                                  |
|-------------------------------------|--------------|---|----------------------------|----------------------------------|
|                                     | Technology   | Date of declaration   | Primary article identifier | Declaration no. in SCIP database |
| LEDriving HL BRIGHT $\triangleq$ H1 | LED          | 19-10-2024  | 4062172315579              | In work                          |

# Product family datasheet

## Download Data

| File  |  |
|---|--|
|  | User instruction<br>LEDiving HL BRIGHT                   |
|  | Brochures<br>LEDiving Retrofits - Exchange overview (EN) |

### Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

### Application advice

For more detailed application information and graphics please see product datasheet.

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

